

# Elcometer 311 Refinishing Gauge



Elcometer 311 Refinishing Gauge

**At a glance**

- Simple, easy-to-use gauge specifically designed for the automotive industry.
- Available in Ferrous only, or Dual FNF versions.

Can be used in accordance with:	
ASTM D 387	ASTM D 332
ISO 8780-5	ISO 787/16
NFT 30 023	

**Elcometer 311 Refinishing Gauge**  
The Elcometer 311 has been specifically designed to meet the requirements of today's automotive market.

The Elcometer 311 is available in two options. The ferrous only instrument is ideal for measuring steel car body panels. The Dual FNF instrument enables the user to take measurements on both steel and aluminium car body panels using one gauge.

Pre-calibrated on steel and aluminium car body panels, the Elcometer 311 is very easy-to-use. Checkpieces are supplied with each instrument to verify its performance.

- Designed specifically to meet the requirements of the automotive industry.
- Ferrous Only and Dual FNF gauges available
- Pre-calibrated on automotive steel and aluminium.
- Bigfoot™ for stable, repeatable readings.
- Scale range of 0-500µm (0- 20mils)
- Auto on/off switch
- Checkpiece included to verify performance – FNF gauge comes complete with ferrous and non-ferrous checkpieces.
- Available in Metric or Imperial Units

**Coating Thickness Gauges- Digital**  
Simple to interpret, small and portable gauges for the measurement of coatings on all metal surfaces. Digital coating thickness gauges are more accurate, more repeatable and more reproducible than any other type of coating thickness gauge on the market today.

Elcometer offers the world's most comprehensive range of portable digital coating thickness gauges - for measurements on either Ferrous substrates (F), Non-Ferrous substrates (NF), or on both Ferrous and Non-Ferrous (FNF), Elcometer can provide you with a gauge to meet your need.

With a wide choice of gauges to choose from, the User needs to understand the terminology of Coating Thickness Gauges or, 'The Language of CTGs'.

THE LANGUAGE OF CTGs

In selecting the most appropriate gauge for your application, you need to answer specific questions.

1. What is the substrate (the surface metal) you are coating/inspecting?

Is the metal a Ferrous Substrate (F) or a Non-Ferrous (NF)? Sometimes this is difficult to answer – the substrate may have already been coated .The easiest way to identify this is to see if a magnet will stick to the surface. If it does, then the substrate will be Ferrous, if it does not, then the substrate is Non-Ferrous.

2. Do you measure only on this substrate?

If you only inspect one type of product, then the answer is yes. If you have a range of products that you inspect, then you need to consider whether they are all of the same type of substrate. You should also consider if you have a future possibility of inspecting other substrates. If so, you should consider an FNF gauge.

		Metric	Imperial
Scale Range		0 - 500µm	0 - 20 mils
Resolution		10µm	0.5 mils
Probe Type		Integral only with auto switch on	
Accuracy		±5% or ±10µm whichever is the greater	±5% or ±1.0 mils whichever is the greater
Operating Temperature		0 to 50°C	32 °F to 120°F
Speed of Readings		30 per minute	
Battery Life (continuous)		20 hours	
Dimensions		56 x 24 x 120mm	2.2" x 0.95" x 4.75"
Weight (including Dry Batteries)		115g	4oz
Part Numbers	Ferrous Only	A311FM	A311FE
	Dual FNF	A311FNFM	A311FNFE

3. What is your Coating / Substrate Combination?

Ensure compatibility of the coating and substrate; whether a coating thickness gauge will provide an accurate reading.

4. Typically what sort of coating thickness do you need to measure?

This will help you select the correct probe scale range - e.g. Scale 1 measures coatings up to 1500µm (60mils).

5. What type of probe do you need?

Depending on your application you can select from:

- Integral Probe (the probe is built into the gauge for accurate single handed measurements on large surface areas, pipes, etc.)
- Separate Probe (the probe is connected to the gauge by a cable for all applications).
- PINIP™ (the separate probe is directly attached to the base of the instrument – providing, in your separate gauge, all the benefits of an integral unit).

Separate Probes can be selected from our wide range to meet your application requirements. These include:

- *Regular Probes:* Including Straight, Right Angle (90°) and Telescopic options
- *Miniature Probes:* Including Straight, Right Angle (90°), 45° Angle all in either long or short versions.

6. Do you need to save your readings for your ISO records, or as proof of inspection to your customer?

Elcometer gauges are available in three options:

- *Basic Gauge* -with simple statistics but no memory or data output
- *Standard Gauge* -with statistics, limited memory and data output
- *Top Gauge* -with statistics, enhanced memory, batching capability and data output

## Related products



Elcometer 345

The Elcometer 345 Coating Thickness Gauge is an incredibly versatile gauge. With a range of probes in both Integral or Separate probe versions for coating thickness measurements on Ferrous (F), Non Ferrous (N) or both Ferrous and Non Ferrous (FNF) Substrates, the Elcometer 345 will have a gauge for your requirements.



Elcometer 456

With its recently enhanced and simplified menu screen options, the Elcometer 456 remains the most advanced hand held coating thickness gauge on the market today. This flagship product is available in any combination of Basic, Standard and Top functionality; together with Integral (built in) and an extensive range of separate plug in probes. With such an extensive range of gauge options, there is an Elcometer 456 to meet your specific application needs.



Elcometer 355

Accuracy, simplicity, versatility and flexibility are the watchwords of the Elcometer 355, a truly state of the art hand-held measuring system packed with time-saving and cost cutting features. The key to the superiority of the Elcometer 355 is its measuring system which features a range of interchangeable Probe Modules capable of an accuracy of  $\pm 1\%$  of the reading on a variety of coatings and substrates.

### ENGLAND

Elcometer Instruments Ltd  
Edge Lane  
Manchester M43 6BU

Tel: +44 (0) 161 371 6000  
Fax: +44 (0) 161 371 6010  
e-mail: [sales@elcometer.com](mailto:sales@elcometer.com)  
[www.elcometer.com](http://www.elcometer.com)

### USA

Elcometer Instruments Inc  
1893 Rochester Industrial Drive  
Rochester Hills Michigan 48309

Tel: +1 248 650 0500  
Toll free: 800 521 0635  
Fax: +1 248 650 0501  
e-mail: [inc@elcometer.com](mailto:inc@elcometer.com)  
[www.elcometer.com](http://www.elcometer.com)

### CANADA

Elcometer Canada Ltd  
PO Box 622, 401 Ouelette Avenue  
Windsor, Ontario N9A 6N4

Tel: +1 248 650 0500  
Toll Free: 800 521 0635  
Fax: +1 248 650 0501  
e-mail: [ca\\_info@elcometer.com](mailto:ca_info@elcometer.com)  
[www.elcometer.com](http://www.elcometer.com)

### ASIA & THE FAR EAST

Elcometer (Asia) Pte Ltd  
896 Dunearn Rd  
Sime Darby Centre #3-09  
Singapore 589472,  
Republic of Singapore

Tel: +65 6462 2822  
Fax: +65 6462 2860  
e-mail: [asia@elcometer.com](mailto:asia@elcometer.com)  
[www.elcometer.com](http://www.elcometer.com)

### BELGIUM

Elcometer SPRL  
Rue Vallée 13  
B-4681 Hermalle /s Ardenteau

Tel: +32 (0)4 379 96 10  
Fax: +32 (0)4 374 06 03  
e-mail: [be\\_info@elcometer.be](mailto:be_info@elcometer.be)  
[www.elcometer.be](http://www.elcometer.be)

### FRANCE

Elcometer SARL  
BP 8-Bou  
60 Rue de la Petite Levée  
45430 Chécy

Tel: +33 (0)2 38 86 33 44  
Fax: +33 (0)2 38 91 37 66  
e-mail: [fr\\_info@elcometer.fr](mailto:fr_info@elcometer.fr)  
[www.elcometer.fr](http://www.elcometer.fr)

### GERMANY

Elcometer Instruments GmbH  
Himmlingstraße 18  
D-73434 Aalen

Tel: +49 (0) 7366 91 92 83  
Fax: +49 (0) 7366 91 92 86  
e-mail: [de\\_info@elcometer.de](mailto:de_info@elcometer.de)  
[www.elcometer.de](http://www.elcometer.de)